



Product Data Sheet

API CF-4 15W-40 Diesel Engine Oil

AMARON HI-LIFE LUBES API CF-4 15W-40 Engine Oil multi-grade diesel engine crankcase oil manufactured from HVI virgin base stock. It is fortified with shear stable viscosity index improver and performance proven engine oil additives. It contains special additive as a result, oil in service does not thicken much, even if the engine runs over a longer period

Applications:

AMARON HI-LIFE LUBES API CF-4 15W-40 recommended for diesel engines meeting Bharat I /Euro I emission norms, manufactured by Caterpillar, Cummins, Tata Motors, Ashok Leyland, Swaraj Mazda, Eicher Etc.

Advantages:

- Easy Starting
- Resists oil thickening
- Reduces fuel consumption
- Reduces maintenance cost
- Protects from rust and corrosion

Performance Level:

- API CF-4

Technical values:

Appearance	Clear and Bright
Kinematic Viscosity@100°C, mm ² /sec	13.5
Viscosity Index	120
Flash Point, COC, °C	200
TBN, mg KOH/gm	6.0
Pour Point, °C	(-)24

In pursuit of continuous improvement, these figures may be changed without notice at the sole discretion of Amaron High Life Lubes. All recommendation and suggestions are without guarantee as condition of use are beyond AREML controls.