



Product Data Sheet

API CH-4 15W-40 Diesel Engine Oil

AMARON HI-LIFE LUBES API CH-4 15W-40 Engine Oil is premium high performance multi grade diesel engine oil manufactured from imported high quality base stocks. It is fortified with specially selected organo metallic detergents and ashless dispersant to combat soot induced oil thickening and wear.

Applications:

AMARON HI-LIFE LUBES API CH-4 15W-40 recommended as extended drain service engine oil for new generation low emission Bharat stage II & III compliant diesel engines manufactured by Ashok Leyland, Tata Motors, Volvo, Caterpillar, Cummins, MAN, MACK, DaimlerChrysler etc. operating under most severe conditions using low or high sulphur diesel fuels.

Advantages:

- Excellent wear protection
- Excellent anti oxidation properties
- Minimizes deposit formation
- Extended drain service interval (up to 60000 km* / 400 HRS*)
- Lowers operating costs Reduces maintenance cost Reduces fuel consumption

(* This is indicative drain period, please refer OEM service manual as per vehicle type)

Performance Level:

- API CH-4

Technical values:

Appearance	Clear and Bright
Kinematic Viscosity@100°C, mm ² /sec	13.5
Viscosity Index	130
Flash Point, COC, °C	220
TBN, mg KOH/gm	8.5
Pour Point, °C	(-)24

In pursuit of continuous improvement, these figures may be changed without notice at the sole discretion of Amaron High Life Lubes. All recommendation and suggestions are without guarantee as condition of use are beyond AREML controls.