

Product Data Sheet

API GL-4 80W-90

AMARON HI-LIFE LUBES API GL-4 80W90 is hypoid Gear Oil formulated to give good oxidation stability for long service life. This oil contains Extreme Pressure (EP) additives to withstand high temperature and pressure encountered during power transmission. In addition, it also contains Pour Point Depressant to prevent the lubricant from channelling at low temperature.

Applications:

AMARON HI-LIFE LUBES API GL-4 80W90 is all season, Extreme Pressure Gear Oils for hypoid gears operating under high speed, high torque conditions.

It is ideal for manual transmissions, rear axle, automotive hypoid gear units and fluid lubricated universal joints and are recommended for Maruti, Premier, HM, Ashok Leyland, Tata Motors, Eicher, M&M, TAFE, Swaraj, Mahindra, Escorts, etc.

Advantages:

- Maximizes equipment life by resisting gear wear and scuffing
- Long service life by resisting oxidation and oil thickening
- Protection against corrosion of ferrous and non-ferrous components
- Prevents loss of lubricant from foaming

Performance Level:

- API GL- 4
- IS: 1118:92
- MIL-L-2105

Technical values:

Appearance	Clear and Bright
Kinematic Viscosity@100°C, mm²/sec	14.5
Viscosity Index	110
Flash Point, COC, °C	200
Pour Point, °C	(-)21

In pursuit of continuous improvement, these figures may be changed without notice at the sole discretion of Amaron High Life Lubes. All recommendation and suggestions are without guarantee as condition of use are beyond AREML controls.