



Product Data Sheet

API SF/CD 20W-50 PCMO ENGINE OIL - CNG Special

AMARON HI-LIFE LUBES API SF/CD 20W-50 CNG is formulated to meet API SL/CF performance requirement. It is blended using high quality base oils, shear stable viscosity improver, performance proven engine oil additives and pour point depressant. Its specially developed for 3W vehicles for their optimum performances.

Applications:

AMARON HI-LIFE LUBES API SF/CD 20W-50 CNG OIL is recommend for use in all LPG /CNG/ Petrol engines 3-wheeler and small delivery vans.

Advantages:

- Compatible with alternative fuel
- Excellent TBN retention
- Low ash forming
- Provides exceptional control of deposit and oil oxidation

Performance Level:

API SF/CD

Technical values:

| | |
|---|-----------|
| Appearance | Clear and |
| Kinematic Viscosity@100°C, mm ² /Sec | 17.5 |
| Viscosity Index | 110 |
| Flash Point, COC, °C, | 220 |
| TBN mg KOH/gm. | 4 |
| Pour Point, °C, Max. | (-) 24 |

In pursuit of continuous improvement, these figures may be changed without notice at the sole discretion of Amaron High Life Lubes. All recommendation and suggestions are without guarantee as condition of use are beyond AREML controls.